



Your comfort. Your safety.



▼ P/N: 9SA0123110A12AM

SCALETTA A 2 RIBALTE - 6 GRADINI L= 1690 mm

BUNK LADDER WITH FOLDING MECHANISM (2 FLAPS) - 6 STEPS L= 1690 mm

Scalette con struttura in alluminio e gradini in materiale plastico confortevole ed ergonomico. Sistema di aggancio/sgancio pratico e veloce sollevando la scaletta per rimuoverla e reinserirla negli appositi riscontri per metterla in posizione di blocco con un unico movimento. Piedino in gomma antiscivolo, adattabile a qualsiasi superficie di appoggio. Massima leggerezza, qualità e sicurezza secondo standard europei. Conformità al regolamento 1646-1. Per il fissaggio del riscontro a parete utilizzare 4 viti Ø3.5 DIN 7505 B, con lunghezza minima di L=18 mm. (Non comprese nella fornitura).

Ladders with an aluminium structure and steps made of comfortable and ergonomic plastic material. Practical and quick attachment/detachment system: simply lift the ladder to remove it and reinsert it into the appropriate holders to put it in locked position with a single movement. Anti-slip rubber foot, adaptable to any bearing surface. Maximum lightness, quality and safety according to European standards. Compliance with regulation 1646-1.


To fix the striker to the wall, use 4 screws Ø3.5 DIN 7505 B, with a minimum length of L=18 mm. (Not included in delivery).

Riferimento a Reg.1646-1:

Le scalette CTA sono progettate e realizzate in conformità al regolamento 1646-1.

Reference to Reg.1646-1:

CTA ladders are designed and manufactured in accordance with Regulation 1646-1.



DATI TECNICI/Technical Datasheet

Dimensioni aperta/Open dimensions

1690x305x55 mm

Dimensioni chiusa/Close dimensions

1051x305x100 mm

Peso/Weight

2.88 kg

Materiale/Materials

Plastica / Plastic - Alluminio / Aluminium

Colore/Colours

Argento / Silver

Conforme alla norma/ Complies with the standard

1646-1



CTA S.R.L.

Via Nicaragua 4 • 00071 Pomezia (RM) Italy • Tel. - Fax 06.91601096



www.cta-europe.com



info@cta-europe.com